essentials™

Technical Specification

Product Code: WA4147 **Description:** 1 Gang 47mm Deep FlameGuard® Dry Lining Box







General Information

Dimensions (mm)	82 (W) x 82 (H) x 35 (D)
Cutout Dimensions (mm)	73 (W) x 73 (H)
Materials	Body: Galvanised Steel Terminal Screw: Brass Pad Insert: Intumescent Composite
	Earth Terminal: Brass Springs : Spring Steel
Minimum Plasterboard Thickness (mm)	5
Maximum Plasterboard Thickness (mm)	30
Back Box Knockouts - Total (mm)	5 x Ø25
Back Box Knockouts - Top (mm)	2 x Ø25
Back Box Knockouts - Bottom (mm)	2 x Ø25
Back Box Earth Terminal Supplied	Yes
Operational Temperature (°C)	-5 to +40
Warranty (Years)	10
Back Box Knockouts - Sides (mm)	None
Back Box Knockouts - Rear (mm)	1 x Ø25

Standards BS EN 1364-1: 2015
BS EN ISO 10140-2: 2010
BS 4662: 2006+A1: 2009

Regulations Part B (Fire)Up To 90 Minutes In Non-Loadbearing Studwall
Part E (Acoustic) & Complies with the requirements published in the Robust Details Part E Handbook

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

Errors & Omissions excluded.
Specification is subject to change without notice.